

The KYTOLA® model TTFH is a sturdy industrial variable area flow meter. It has a stainless steel body with a heavy-duty impact resistant acrylic flow tube. It is a reliable instrument for measuring and monitoring large water flows.



- Flow rate water up to 1000 L/min
- Maximum pressure 16 bar
- Maximum temperature 75°C
- Minimum temperature seals -30°C nitrile, -20°C Viton®
- Flange connections DN 80

FLOW METER TTFH

FEATURES

- Sturdy construction
- Stainless steel body
- Acrylic (PMMA) impact resistant flow tube

TYPICAL APPLICATIONS

- Water treatment
- Power plants
- Swimming pools

OPTIONS

- Viton®, EPDM seals
- Special scale markings

Model	TTFH
Connections	DN 80 flanges
Max pressure	16 bar
Max temperature	70°C
Body	AISI 316
Float	AISI 329 Note! Other possible wetted metal parts: AISI 316
Flow tube	Acrylic
Seals	Nitrile (*Viton®, *EPDM)
Weight	17.5 kg
Accuracy	± 5% F.S.
	*) Special construction on request

TT			
Connections			
DN 80 flanges	FH		
Flow Range H₂O L/min			
75–600		4A	
100–1000		4B	
Scale			
H ₂ O L/min at +20°C			A
Special Feature			
Viton® seals			V
EPDM seals			Y

